[54]		AND APPARATUS FOR ER GENERATION		
[75]	Inventor:	Eric S. Prame, Lidingo, Sweden		
[73]	Assignee:	International Business Machines Corp., Armonk, N.Y.		
[21]	Appl. No.:	95,897		
[22]	Filed:	Nov. 19, 1979		
[30]	Foreign	n Application Priority Data		
Nov. 21, 1978 [SE] Sweden 78119831				
[51] [52]	Int. Cl. ³ U.S. Cl			
[58]	340/365	arch 340/365 S, 365 R, 365 E, A; 178/17 R, 17 A, 17 C, 79; 179/90 R, 2 DP; 400/100, 472, 485, 486, 489		
[56]		References Cited		
	U.S. I	PATENT DOCUMENTS		
	3,225,883 12/1 3,892,915 7/1 3,932,838 1/1			

3,967,273 6/1976 Knowlton 340/365 S

3,973,256	8/1976	Stoesser 340/365 S
4,007,443	2/1977	Bromberg et al 340/365 S
4,012,599	3/1977	Meyer 179/2 DP
4,042,777	8/1977	Bequaert et al 340/365 R

OTHER PUBLICATIONS

Conway et al., "Communications of the ACM", vol. 10, No. 9, Sep. 1967, p. 539.

Primary Examiner—John W. Caldwell, Sr. Assistant Examiner—Donnie L. Crosland Attorney, Agent, or Firm—Edward H. Duffield

[57] ABSTRACT

Generation of a character code for an alphabetic character is performed by depressing at least two keys in a sequence. The code is generated when the last key is depressed and the other keys in the sequence still are pressed, or when all keys in the sequence are released. Numerical character codes are generated by depressing only one key per character. A logic and storage means is provided having a number of registers, code converting tables and control circuits for storing the history of depressed keys and for generating character codes.

6 Claims, 6 Drawing Figures

